

YZ-H762

羟基丙烯酸树脂

特性

- 1、干性快
- 2、硬度高
- 3、耐候优异

用途

应用于高硬度 VOC 低于 480 清漆，亦可拼用常规 60/65/70 固含低粘中高羟树脂，制备 VOC 低于 480 清漆。低 VOC 色漆

性质

特性	数值	单位
组份	丙烯酸共聚物	
外观	清澈透明	
固体份	75±2	%
黏度	2000-4000	mPa.s/25°C
酸值	3-7	mgKOH/g
溶剂	BAC/XYL	
色号	≤1(Fe-Co)	
羟基含量	4.5(固体份)	%

储存说明

- 远离热及火源，置于阴凉通风处，容器保持紧密。
- 本产品自生产日起，保质期限为 12 个月。

包装规格

200kg/桶

安全

本产品含溶剂，必须做好防护措施，小心操作，避免接触皮肤与眼睛，其它详细资料请参考物质安全说明书。

以上资料系经试验所得，仅供参考，不作任何保证之用。鉴于树脂功能的局限性及用户要求的多样性，若使用公司产品，使用前请按自身的要求严格试验树脂的适应性及最终产品的稳定性。

版本：2025-5-29

YZ-H762

Hydroxyl Acrylic Resins

Characteristics

- 1、 Fast drying
- 2、 High hardness;
- 3、 Good weather resistance

Application

Property Applied to high hardness VOC lower than 480 varnish, it can also use conventional 60 / 65 / 70 solid resin with low viscosity and high hydroxy resin to prepare VOC lower than 480 varnish. Low VOC color paint

Characteristics	Numeric value	Unit
Component	Acrylic copolymer	
Appearance	Clear and bright	
Solid Content	75±2	%
Viscosity	2000-4000	mPa.s/25°C
Acid Value	3-7	mgKOH/g
Solvent	BAC/XYL	
Color	≤1(Fe-Co)	
OH Content	4.5	%

Storage instructions

- Keep away from fire and heat, placed in a cool and ventilated place, Keep the container tightly sealed.
- Shelf time:12 months.

Packing

200Kg/Bucket

Safety

This product contains solvent, you must take protective measures , avoid contacting with skin and eyes, other information please refer to the material safety instruction.

The above information is obtained through experiments. It is provided for reference only. Given the limitations of resin functionality and the diversity of user requirements.If you use our products, please strictly verify according to your own requirements .Please strictly test the adaptability of the resin and the stability of the final product according to your own requirements.

Version: 2025-5-29

Jiafu Industrial Zone Yinshan Industrial Park high-tech zone Qingyuan City Guangdong Province China

Tel: 0763-3607328 E-mail: liushul@yakoo.com.cn [Http://www.yakoo.com.cn](http://www.yakoo.com.cn)